

GRE liner

Repsa GRE liner has been developed to be used as internal lining in tubing or line pipe, when it is necessary to operate with corrosive fluids such as condensation water, purge water, formation water, crude oil, CO₂, H₂S, etc.

Available in a standard length of 32 to 32.80 ft.

Applications

- Injection wells (water, CO₂, polymers).
- Production wells
- Sump wells.

Benefits

- Inexpensive solution against tubular CRA (Corrosion-Resistant Alloy).
- Product design validated for more than 20 years under most severe operating conditions.
- High durability corrosion protection system.

- Excellent abrasion resistance compared to other liners systems available on the market (thermoplastic coatings or liners such as PE or PP).
- Applicable in pipes with any joint system (standard and premium threads)

| DIAMETER INCHES | INNER DIAMETER | | ESPESOR MÍNIMO LINER | | INNER DIAMETER TAPAS (DIT) | |
|--------------------|----------------|--------|----------------------|--------|----------------------------|--------|
| | INCHES | MM | INCHES | MM | INCHES | MM |
| 2 3/8" | 1,81 | 45,97 | 1,81 | 45,97 | 1,81 | 45,97 |
| 2 7/8" | 2,23 | 56,64 | 2,23 | 56,64 | 2,23 | 56,64 |
| 3 1/2" | 2,69 | 68,33 | 2,69 | 68,33 | 2,69 | 68,33 |
| 4 1/2" | 3,69 | 93,75 | 3,69 | 93,75 | 3,69 | 93,75 |
| 5" | 4,01 | 101,85 | 4,01 | 101,85 | 4,01 | 101,85 |
| 5 1/2" | 4,68 | 118,75 | 4,68 | 118,75 | 4,68 | 118,75 |
| 7" | 5,90 | 149,86 | 5,90 | 149,86 | 5,90 | 149,86 |